

1. INSULATION

EXL = AccuTru Premium
High Purity, Extended Life
Special Limits of Error
MGO = Magnesium Oxide
Special Limits of Error

2. CALIBRATION

K = Type K
J = Type J
N = Type N
T = Type T
E = Type E
DK = Dual Type K
DJ = Dual Type J
DN = Dual Type N
DT = Dual Type T
DE = Dual Type E

3. JUNCTION

U = Ungrounded
G = Grounded
E = Exposed

4. SHEATH MATERIAL

600A = Alloy 600
316S = 316 SS
310S = 310 SS
304S = 304 SS
446S = 446 SS
276C = Hastelloy C276
HASX = Hastelloy X
TITN = Titanium
* Contact factory for other materials

5. SHEATH DIAMETER

062D = 0.062
125D = 0.125
188D = 0.188
250D = 0.250
375D = 0.375

* Contact factory for other diameters

6. SENSOR LENGTH

Dim A
(inches xxx.xx)

7. TERMINATION


B = Bare Wire 3" Stripped Leads w/ PVC Color Coded Heat Shrink

8. LEAD WIRE LENGTH

X = Not Applicable with Bare End Termination

9. LEAD WIRE INSULATION

X = Not Applicable with Bare End Termination



10. WELDED HEX NIPPLE OPTIONS

X = NONE
H4 = 1/4" NPT SS
H6 = 3/8" NPT SS
H8 = 1/2" NPT SS
H12 = 3/4" NPT SS

11. NOT REQUIRED

X = NOT USED

12. OPTIONS

X = NONE
SEE PAGE 1-A FOR OTHER OPTIONS